


Low Vcesat NPN Epitaxial Planar Transistor


Features:

- Low $V_{CE(sat)}$, $V_{CE(sat)}=0.1\text{ V}$ (typical), at $I_C / I_B = 1\text{ A} / 50\text{ mA}$
- Excellent current gain characteristics
- Complementary to BTB1424AM3
- Pb-free lead plating package

SOT-89



BV_{CEO}	50V
I_C	3A
$R_{CE(SAT)}$ typ.	125m Ω



B : Base
C : Collector
E : Emitter

Ordering Information

Device	Package	Shipping
KMD2150A	SOT-89 (Pb-free lead plating and halogen-free package)	1000 pcs / Tape & Reel

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-Base Voltage	V _{CB0}	80	V
Collector-Emitter Voltage	V _{CEO}	50	V
Emitter-Base Voltage	V _{EBO}	6	V
Collector Current	I _C	3	A
Collector Current (pulse)	I _{CP}	7	A
Power Dissipation	P _d	0.6	W
		1 *1	
		2 *2	
Operating Junction Temperature Range	T _j	-55~+150	°C
Storage Temperature Range	T _{stg}	-55~+150	°C

Note : *1 Printed circuit board, 1.7mm thick, collector copper plating 10mm*10mm.

*2 When mounted on a 40*40*0.7mm ceramic board.

Characteristics (Ta=25°C)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV _{CB0}	80	-	-	V	I _C =50μA, I _E =0
BV _{CEO}	50	-	-	V	I _C =1mA, I _B =0
BV _{EBO}	6	-	-	V	I _E =50μA, I _C =0
I _{CB0}	-	-	0.1	μA	V _{CB} =60V, I _E =0
I _{EBO}	-	-	0.1	μA	V _{EB} =5V, I _C =0
*V _{CE(sat)}	-	0.1	0.25	V	I _C =1A, I _B =50mA
*V _{CE(sat)}	-	0.25	0.5	V	I _C =2A, I _B =0.2A
*R _{CE(sat)}	-	0.125	0.25	Ω	I _C =2A, I _B =0.2A
*V _{BE(sat)}	0.8	1	1.5	V	I _C =2A, I _B =0.2A
*h _{FE1}	180	-	-	-	V _{CE} =2V, I _C =0.1A
*h _{FE2}	180	-	820	-	V _{CE} =2V, I _C =0.5A
*h _{FE3}	100	-	-	-	V _{CE} =2V, I _C =1A
f _T	-	90	-	MHz	V _{CE} =5V, I _C =0.1A, f =100MHz
Cob	-	45	-	pF	V _{CB} =10V, f=1MHz


*Pulse Test : Pulse Width ≤380μs, Duty Cycle≤2%

Classification Of h_{FE} 2


Rank	R	S	T
Range	180~390	270~560	390~820

Typical Characteristics


Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics




Emitter Grounded Output Characteristics






Current Gain vs Collector Current




Saturation Voltage vs Collector Current



Typical Characteristics(Cont.)




Recommended soldering footprint




unit : mm

Reel Dimension




Unit: millimeter

Carrier Tape Dimension




Unit : millimeter

SOT-89 Dimension



Marking:



Style: Pin 1. Base 2. Collector 3. Emitter

3-Lead SOT-89 Plastic
Surface Mounted Package

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1732	0.1811	4.40	4.60	F	0.0591	TYP	1.50	TYP
B	0.1551	0.1673	3.94	4.25	G	0.1181	TYP	3.00	TYP
C	0.0610	REF	1.55	REF	H	0.0551	0.0630	1.40	1.60
D	0.0906	0.1024	2.30	2.60	I	0.0138	0.0173	0.35	0.44
E	0.0126	0.0205	0.32	0.52					